

The Senko Single Gas Detector SGT-P

Replaceable Sensor & Battery type



SENKO

The most classic detector with a reliable and durable 2 years lifespan and a cost-effective price

The Senko SGT-P Series is a Replaceable single-gas detector that user can replace a sensor or battery after 2-years lifespan. You can turn off the device whenever and battery life signal will let you know when it is time to replace the battery.

High-Sensitivity sensor in SGT-P delivers the real-time reading in ppm (0.1ppm resolution for H2S) and high performing alert provides the ultimate protection from gas poisoning. SGT-P also features a simple menu tree and clear sign of malfunction.

Compatible with IR-Link communication and the Docking Station II, the Senko SGT-P Series is ideal for workers in hazardous areas who need to stay safe with easy way.



Specification

Model	SGT-P
Sensor Type	Electrochemical
Gas Type	O2, H2S, CO, NH3, H2, SO2, NO2,CL2, HCN, HCL, PH3
Measurement	Diffusion type
Display	LCD display
Audible	90dB at 10cm
Warning Lamp	Red Flashing LEDs (Light-Emitting Diode)
Vibration	Vibration Alarm
Battery	Manufacture: Vitzrocell P/N: SB-AA02(P) / System: Lithium Primary Battery Nominal voltage: 3.6V / Nominal capacity: 1.2Ah
Temperature	-40°C ~ +50°C(for Toxic) / -35°C ~ +50°C(for O2)
& Humidity	5%~95% RH (Non-condensing)
Case	Rubber Enclosure
Accessories	Calibration Cap, Manual, Calibration and Quality report
Option	External Sampling Pump (SP-Pump101), SENKO-IR Link, Docking Station
Size & Weight	Size: 54(W) × 91(H) × 32(D)mm Weight: 93g(Toxic), 104g(O2) (Battery, clip included)
Operating Life	24 months, based on 2 minutes of alarm per day
Event Log	Recent 30 alarms
Approval	ATEX II 1 G Ex ia IIC T4 Ga IECEX Ex ia IIC T4 Ga INMETRO Ex ia IIC T4 Ga



Standard Package Contents

- Detector complete with stainless steel alligator clip
- Calibration cap
- User manual
- Calibrate test certification

Accessories

SGT-P Docking station

Automatic functional Bump & Calibration test up to 4 units. Save your time and gas usage.



SGT-P
Docking station



IR-Link

IR-Link communication

User can change alarm set points and upload firmware updates and download event logs and perform calibration. For use with SGT series and MGT.

