







|                               |   |
|-------------------------------|---|
| <b>Model</b>                  | SI-200E   |
| <b>Dimensions</b>             | 169mm (W) x 188.5mm (D) x 107mm (H)   |
| <b>Weight</b>                 | 2.4kg   |
| <b>Sensors</b>                | O2, Toxic Gas and Combustible Gas   |
| <b>Operation Power</b>        | DC: +24Vdc ± 10%  |
| <b>Power Consumption</b>      | 3.6W @+ 24VDC   |
| <b>Operation Mode Display</b> | FND, Concentration of Gas, Alarm, Malfunction   |
| <b>Relay</b>                  | 1 <sup>st</sup> Alarm, 2 <sup>nd</sup> Alarm, Fault Alarm (Rated 2.0A@30vdc)                      |
| <b>Analog Output Signal</b>   | 4-20mA  |
| <b>Digital Output Signal</b>  | RS-485  |
| <b>Measuring Type</b>         | Diffusion   |
| <b>Operating Temperature</b>  | -40°C ~ 60°C  |
| <b>IP</b>                     | IP66  |
| <b>Input &amp; Setting</b>    | 4 Buttons & RS-485 & Bluetooth  |
| <b>Device Warranty</b>        | 2 years   |
| <b>Sensor Warranty</b>        | 1 year  |
| <b>Wireless Interface</b>     | RS-485 Modbus, HART (Option)  |
| <b>Certification</b>          | ATEX II 2 G Ex db IIC T6 Gb<br>IECEx Ex db IIC T6 Gb<br>Etc. EMC, RoHs2, RCM(ACMA&RSM), FCC, SIL2 |



**DIMENSION (Unit:mm)**



**SENKO**

More information:  
[latest@senkoeurope.com](mailto:latest@senkoeurope.com)  
 +44 191 829 9930